



**Terry**   
total mobility solutions

# MELODY 2 LIFTING PLATFORM

## Melody 2 non-enclosed Lifting Platform

The Terry Melody 2 Lifting Platform offers an aesthetically pleasing solution to the problem of short-rise vertical wheelchair access outside and inside public buildings (or, where appropriate, domestic household situations). The innovative design ensures that special emphasis has been placed on the needs of both the lift user and the building owner in facilitating compliance with the current disability legislation.

### Complies with Part M of the Building Regulations and meets the requirements of the Disability Discrimination Act

- Emergency lowering facility
- Call and send buttons on landing
- Polycarbonate infill panels
- No enclosure or support tower required
- Integral ramp eliminates the requirement for a pit – minimises building work
- Lift carriage finished in attractive, durable stainless steel
- 1100 x 1400 Platform available as an option
- RAL colours available as an option
- Security options available e.g. Radio Enabler and Radio Isolate
- Alarm

### Standard Specification

**Application range:** People with impaired mobility and Wheelchair users. Internal & External Locations

**Maximum safe working load:** 500Kg

**Maximum travel:** 2m (2000mm) 3m (3000mm) domestic

**Rated speed:** 0.08 metres per second

**Power supply electrical requirements:**  
 220 / 240V~50 / 60 Hz-13A single phase (max).  
 Dedicated RCD protected supply

**Low voltage control system:** 12VDC

**Operating temperature range:** -10°C to +40°C

**Safety:** Full platform safe edge which stops the lift should it touch any obstacle in the down direction only. Protects against entrapment below the platform and inside the guide. Fully interlocked upper and lower gates

**Drive:** Direct acting hydraulic

## Melody 2 Lift Dimensions (in mm)

